





Isuzu 20 KVA Silent Build Up SPECIFICATION

DETAIL SPECIFICATION	
Capacity	20 KVA/ 16 KW
Engine Manufacturer	ISUZU
Number of Cylinder	4
Cylinder Arrangement	In-Line
Cycle	4 Stroke
Displacement (L)	2.771
Aspiration	Natural
System of Starting	Electric with Accu
System of Cooling	Water-Cooled
Combustion System	Direct Injection
Number of Phase	3 (Three)
Bore and stroke (mm)	93 x 102
Oil Consumption (L)	5.5
Solar Consumption 75% (L/H)	4.6
Solar Consumption 100% (L/H)	6.2
Tank Capacity (L)	50
Compression Ratio	18.2:1
Winding Pitch	TWO THIRDS
Rated Speed	1500 rpm
Rated Frequency	50 Hz
Rated Voltage	220/380V







Isuzu 20 KVA Silent Build Up SPECIFICATION



DIMENSION SILENT TYPE		
Length (mm)	2000	
Width (mm)	950	
Height (mm)	1250	
Weight (kg)	796	







Isuzu Silent Build Up DEEPSEA



DEEPSEA

Standard Control Panel Deepsea uses micro processing technique integrating digital, intelligent and network techniques which can carry out functions including auto start/stop, data measure, alarming. The controller uses LCD display.

Otional Chinese and English display interface with operation easy and reliable. It can be widely used in all types of generator automatic control system for compact structure, advanced circuits, simple connections and high reliability

WORKSHOP IN 4 CITY

> TANGERANG

SEMARANG <

Jl. Daan mogot KM 22 no 1 Batu Ceper. > Surabaya

Kawasan Industri Candi Gatot Subroto Blok 12 no 6. BALI <

Margomulyo Permai Blok AB no 62.

Jln Mahendaradata Selatan no 18X Denpasar.

